

(19) World Intellectual Property
Organization
International Bureau



(43) International Publication Date
3 March 2005 (03.03.2005)

PCT

(10) International Publication Number
WO 2005/019890 A1

(51) International Patent Classification⁷: **G02B 6/255**

(21) International Application Number:
PCT/US2004/023262

(22) International Filing Date: 19 July 2004 (19.07.2004)

(25) Filing Language: English

(26) Publication Language: English

(30) Priority Data:
2003-207134 11 August 2003 (11.08.2003) JP

(71) Applicant (for all designated States except US): **3M INNOVATIVE PROPERTIES COMPANY** [US/US];
3M Center, Post Office Box 33427, Saint Paul, Minnesota
55133-3427 (US).

(72) Inventors; and

(75) Inventors/Applicants (for US only): **YAMAUCHI,**

Takaya [JP/JP]; 3-26-23, Tanashioda, Sagamihara, Kanagawa 229-1125 (JP). **YAZAKI, Akihiko** [JP/JP]; 3-26-10 Minamino, Hachioji, Tokyo 192-0916 (JP).


(74) Agents: **ROSENBLATT, Gregg, H.** et al.; Office of Intellectual Property Counsel, Post Office Box 33427, Saint Paul, Minnesota 55133-3427 (US).

(81) Designated States (unless otherwise indicated, for every kind of national protection available): AE, AG, AL, AM, AT, AU, AZ, BA, BB, BG, BR, BW, BY, BZ, CA, CH, CN, CO, CR, CU, CZ, DE, DK, DM, DZ, EC, EE, EG, ES, FI, GB, GD, GE, GH, GM, HR, HU, ID, IL, IN, IS, KE, KG, KP, KR, KZ, LC, LK, LR, LS, LT, LU, LV, MA, MD, MG, MK, MN, MW, MX, MZ, NA, NI, NO, NZ, OM, PG, PH, PL, PT, RO, RU, SC, SD, SE, SG, SK, SL, SY, TJ, TM, TN, TR, TT, TZ, UA, UG, US, UZ, VC, VN, YU, ZA, ZM, ZW.

(84) Designated States (unless otherwise indicated, for every kind of regional protection available): ARIPO (BW, GH, GM, KE, LS, MW, MZ, NA, SD, SL, SZ, TZ, UG, ZM, ZW), Eurasian (AM, AZ, BY, KG, KZ, MD, RU, TJ, TM),

[Continued on next page]

(54) Title: OPTICAL FIBER CONNECTING DEVICE



(57) Abstract: An optical fiber connecting device (10) has a pair of holding elements (44) which are formed on an actuating member (16) and are capable of undergoing elastic deformation as a sheath holding mechanism for securing, to a body (12), the sheath portions (S) of the optical fibers (F) having uncoated fiber elements (C) to be held by the fiber-element securing member (14). The holding elements (44) form a pair of passages for guiding the optical fibers (F) on the body (12). The holding elements (44) undergo the elastic deformation accompanying the motion, on the body (12), of the actuating member (16) for closing the fiber-element securing member (14), and push and hold the sheath portions (S) of the optical fibers (F) in the corresponding passages by utilizing their own elastic restoring forces. Each holding element (44) includes a pressing part (54) formed at a free end separated away from a fixed end part (52), and an engaging part (56) positioned between the fixed end part (52) and the pressing part (54). The optical fiber connecting device can have a reduced number of parts and can provide a stable sheath-holding function without being affected by dimensional errors in the constituent parts.



European (AT, BE, BG, CH, CY, CZ, DE, DK, EE, ES, FI, FR, GB, GR, HU, IE, IT, LU, MC, NL, PL, PT, RO, SE, SI, SK, TR), OAPI (BF, BJ, CF, CG, CI, CM, GA, GN, GQ, GW, ML, MR, NE, SN, TD, TG).

For two-letter codes and other abbreviations, refer to the "Guidance Notes on Codes and Abbreviations" appearing at the beginning of each regular issue of the PCT Gazette.

Published:

— *with international search report*